



Digital Security System

## 2/5 Megapixel 12x/23x H.265 PoE Mini PTZ Dome Network Camera




### KEY FEATURES

- ▶ **Smart Stream** (Bandwidth, storage and bit rate save with Smart Stream ON, eg, H.265+ save 70%~80% bandwidth of H.264.)
- ▶ **0.002Lux Starlight** (Deliver high detailed color images even in low light environment reaching 0.002Lux.)
- ▶ **140dB Super WDR** (Excellent performance even when the ratio of the luminosity of brightest and darkest is up to 140dB)
- ▶ **Advanced Functions** (Boasting to support various advanced functions such as HLC, Defog, ROI.)
- ▶ **Smart PTZ Motion Detection** (Pan and tilt to the position of motion detected area automatically and zoom in synchronously)
- ▶ **255 Preset Positions** (The user can easily control the lens position via mouse to monitor interested area and set up to 255 preset positions for patrolling.)
- ▶ **Video Content Analysis** (With 10 detection modes, VCA greatly enhances the performance bringing comprehensive surveillance functions.)
- ▶ **Keyboard Control** (Shortcut keys for PTZ control via keyboard.)

### 12x/23x CdhjW Ncca

The 12x/23x optical zoom can zoom up to distant subjects while still maintaining the clarity, delivering high quality video over the entire zoom range.




### Smart IR II Technology

It allows the camera to catch better images regardless of object distance with High Beams and Low Beams whose brightness could be adjusted. Anti-reflection Panel protects the lens from IR interference.

### High Speed & Precise Movement

With a sophisticated pan/tilt mechanism, the 12x/23x H.265 Mini PoE PTZ Dome Network Camera provides fast, precise movement with 360° endless pan and -5 ~ 90° (Auto Flip). Maximum pan speed of 240°/s and tilt speed of 200°/s make the camera a mighty Speed Dome model.



### Recessed Installation

With recessed installation, the 12x/23x H.265 Mini PoE PTZ Dome Network Camera is easily blend in with the environment to provide discreet surveillance.

# 12x/23x H.265 Mini PTZ Dome Network Camera









|         | Model                     | DI-MS212<br>(2MP/12x)   | DI-MS223<br>(2MP/23x)                   | DI-MS512<br>(5MP/12x)   |
|---------|---------------------------|---|---|---|
| Camera  | Image Sensor              | 1/2.8" Progressive Scan CMOS  |   |   |
|         | Min. Illumination         | Color: 0.002Lux@F1.2<br>B/W: 0Lux with IR on  |   | Color: 0.005Lux@F1.2<br>B/W: 0Lux with IR on                      |
|         | WDR                       | 140dB Super WDR   |   | 120dB Super WDR   |
|         | Shutter Time              | 1/100000s~1s  |   |   |
|         | Day&Night                 | ICR Filter Auto Switch  |   |   |
|         | S/N                       | >55dB   |   |   |
|         | Digital Zoom              | 16x   |   |   |
| Lens    | Focal Length              | 5.3~64mm @F1.6~F2.8,<br>12x Optical Zoom  | 5~117mm @F1.5~F3.5,<br>23x Optical Zoom | 5.3~64mm @F1.6~F2.8,<br>12x Optical Zoom                          |
|         | Zoom Speed                | Approx 3.1s (Optical Wide-Tele)   |   |   |
|         | Field of View             | H61°~H5°/D69°~D5°/<br>V36°~V2°  | H60°~H3°/D69°~D4°/<br>V35°~V2°          | H57°~H4°/<br>V44°   |
|         | Minimum Working Distance  | 1000~1500mm (Wide-Tele)(5.3~64mm) / 100~1500mm (Wide-Tele)(5~117mm)   |   |   |
| PTZ     | Pan Range / Pan Speed     | 360° endless; Pan Manual Speed: 0.5°~180°/s, Pan Preset Speed: 240°/s   |   |   |
|         | Tilt Range / Tilt Speed   | -5°~90° (Auto Flip); Tilt Manual Speed: 0.5°~120°/s, Tilt Preset Speed: 200°/s  |   |   |
|         | Proportional Zoom         | Support   |   |   |
|         | Preset Quantity           | 255   |   |   |
|         | Preset Freezing           | Support   |   |   |
|         | Patrol                    | 8 Patrols, up to 48 presets each patrol   |   |   |
|         | Pattern                   | 4 Patterns  |   |   |
|         | Power Off Memory          | Support   |   |   |
|         | PTZ Position Display      | ON/OFF  |   |   |
|         | 3D positioning            | Support   |   |   |
| IR      | IR Distance               | Up to 120m  |   |   |
|         | IR Angle                  | Auto/Manual   |   |   |
| Video   | Max. Image Resolution     | 1920x1080   |   | 2592x1944   |
|         | Primary Stream            | 60fps@(1920x1080, 1280x960, 1280x720, 704x576)  |   | 30fps@(2592x1944), 60fps@(1920x1080, 1280x960, 1280x720, 704x576) |
|         | Secondary Stream          | 30fps@(704x576, 640x480, 640x360, 352x288, 320x240, 320x192, 320x176)   |   |   |
|         | Tertiary Stream           | 30fps@(1920x1080, 1280x720, 704x576, 640x480, 640x360, 320x240, 320x192, 320x176)   |   |   |
|         | Video Compression         | H.265+/H.265(HEVC)/H.264+/H.264/MJPEG   |   |   |
|         | Video Bit Rate            | 16Kbps~16Mbps(CBR/VBR Adjustable)   |   |   |
|         | Image Setting             | Brightness/Contrast/Saturation/Sharpness  |   |   |
| Network | Ethernet                  | 1*RJ45 10M/100M Ethernet Port   |   |   |
|         | Network Storage           | NAS(Support NFS, SMB/CIFS)  |   |   |
|         | Protocol                  | IPv4/IPv6, TCP, UDP, RTP, RTSP, RTCP, HTTP, HTTPS, DNS, DDNS, DHCP, FTP, NTP, SMTP, SNMP, UPnP, SIP, PPPoE, VLAN, 802.1x, QoS, IGMP, ICMP, SSL                        |   |   |
| Audio   | Audio Compression         | G.711/AAC   |   |   |
|         | Audio I/O                 | 1/1   |   |   |
| System  | Alarm I/O                 | 1/1   |   |   |
|         | RS485                     | Support   |   |   |
|         | Storage                   | Support microSD/SDHC/SDXC Card Local Storage, up to 256G  |   |   |
|         | Advanced Function         | Auto Tracking, Privacy Masking, BLC, HLC, 2D DNR, 3D DNR, ROI, Defog, AWB, EIS, IP Address Filtering, AGC, Anti-flicker, Corridor Mode, Deblur                        |   |   |
|         | SIP/VoIP Support          | Yes, Voice & Video-over-IP  |   |   |
|         | Event Trigger             | Motion Detection, Network Disconnection, External Input, Audio Alarm, etc.  |   |   |
|         | Event Action              | FTP Upload, SMTP Upload, SD Card Record, External Output, SIP Phone, PTZ Motion, HTTP Notification, etc.  |   |   |
|         | Video Analysis (Optional) | Region Entrance, Region Exiting, Advanced Motion Detection, Tamper Detection, Line Crossing, Loitering, Human Detection, People Counting, Object Left, Object Removed |   |   |
|         | System Compatibility      | ONVIF Profile S & G & T   |   |   |
| General | Working Condition         | Temperature: -40℃~60℃ / Humidity: 0~90%(Non-condensing)   |   |   |
|         | Power Supply              | PoE (802.3at) / DC 12V/2A±10%   |   |   |
|         | Power Consumption         | 9W MAX/12W MAX (With IR on)   |   | 11W MAX/14W MAX (With IR on)                                      |
|         | Weather Proof/Housing     | Up to IP66-rated for Weather-resistant Performance / Vandal-proof IK10-rated Metal Housing  |   |   |
|         | Surge Protection          | 4KV   |   |   |
|         | Dimensions/Weight         | Φ183mmX174.8mm/2Kg  |   |   |

# 12x/23x H.265 Mini PTZ Dome Network Camera



## Structure Diagrams



Units: mm

## Accessories Support

A43 Junction Box

Weight: 1000g  
Dimensions: 195\*164\*80mm



A77 Wall Mount

Weight: 650g  
Dimensions: 262\*185\*138mm



A78 Recessed Mount

Weight: 715g  
Dimensions: 256\*256\*94mm



A79 Pendant Mount

Weight: 850g  
Dimensions: 256\*256\*245mm

