

Slim All in One Reader

Can install Optional (Smart Reader Modules + Bluetooth + QR Code)
With Optional Tempered Glass Cover Protector

DI-OBQ-102L



Solutions for a New Era of Access Control

DI-OBQ-102L reader bracket with size suitable for different type of reader module provides card reader + QR Code reader to its well established and powerful access control systems. These ALL IN ONE card reader easily fit into most standard installation..

These Reader is designed for the on-line operation and have no decision authority at all. It will be connected to the IP Master Single Door Controller CCS-IPDC and Slave Single Door Controller CCS-S-DC, which checks, interprets and evaluates the badge content and release the corresponding door.

The readers, which can be easily mounted and in-stalled, read contactless media as Smart Card, Blue-tooth and QR Code. They are equipped with one power LED and a buzzer to visualizes the operation mode.

Feature

- Simple installation
- Multi Reader Technologies
- Audio and visual response
- Automatic energy saving mode
- Artwork can be customized

Reader Interface Functionality

- WIEGAND 44bit
- RS485

Suggested Cable : Shielded Twisted Paris AWG22

Specification

- Power Supply: 12VDC , 250mA Max
- Operation Temperature: -20°C to 70°C
- Storage Temperature: -40°C to 80°C
- Humidity 10—95% RH (non-condensing)
- IP Rating IP65
- Flush Mounted 92 x 180 x 11 mm (Inside Wall 40mm)

